

# Getinge Assured

## Wash Monitor F Holder

The Getinge Assured Wash Monitor F Holder is an auxiliary device for routine monitoring of automated wash processes for hollow instruments in washer-disinfectors and ultrasonic washers.

Wash Monitor F Holder should only be used with Wash Monitor F/R indicators (in washer-disinfectors) or Wash Monitor U/L indicators (in ultrasonic washers). The Wash Monitor F/R or Wash Monitor U/L is inserted into the Wash Monitor F Holder, simulating contaminated flexible hollow lumen instruments.

### Performance Characteristics

The Wash Monitor F/R or Wash Monitor U/L is inserted into the Wash Monitor Holder F. The Holder is then attached to a luer lock connector located on the washer rack. A standard load of hollow lumen instruments is processed as per manufacturer’s recommendations. After wash cycle is complete, results of the cleaning efficacy are displayed on the Wash Monitor F/R and Wash Monitor U/L. The removal of all test soil indicates effective cleaning.



### Physical Characteristics

Wash Monitor F Holder is made of polished stainless steel and silicone.

- **Dimensions:** 1067 mm x 11 mm
- **Weight:** 73 g
- **Substrate Material:** Electro polished stainless steel AISI 304 and silicone conforming quality standards according to European specification ST-EC-60-001.

### Shelf Life

Not applicable.

### Ordering Information

Getinge Assured	Ordering number
Wash Monitor F Holder	503865100